

LASERMARK®

ILMXT Indoor-Outdoor Self-Leveling Laser Cross Level

Projects bright, self-leveling
level and plumb laser
"chalkline" for instant
accurate reference marks



58-ILM-XT

CST/berger

No One Measures Up ... Worldwide

LASERMARK®



Magnetic Laser Tripod Quickly attaches to metal surfaces.



Interior-Exterior

The **iLMXT** is the ideal laser line layout tool for both interior and exterior applications. Easy-to-use operation features horizontal (level) and vertical (plumb) for both interior and exterior jobs, as well as laser cross and manual mode for interior applications. Outdoor "Pulsing" Mode feature provides easy range is over 100-ft when used with detector.

USE FOR:

- Finish carpentry
- Cabinets and shelving
- Installing closets
- Floor and wall tiles
- Wainscoting and paneling
- Drop ceilings
- Remodeling projects
- Door and window frames
- Wallpaper, stencil work
- Wall layout, partitions
- Masonry work
- Electrical: track lighting, overhead, recessed lighting, lighting outlets
- Wall hangings: artwork, switches, lighting, photos, collectibles

Extra-Bright Diodes with Angled Window for Extended Vertical Plumb Line



• **Outdoor Mode**
(Use with Detector)

• **Horizontal Beam Indicator**— Easily align laser with objects for transfer of points

• **Robust Over-Molded Housing**— For Durability and Waterproof (IP55)



Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50 dated July 26, 2001

This LaserMark® product is made to Class 2M or 3R specifications. This unit ships a Class 2M unless specified otherwise. Specifications subject to change without notice.

iLMXT

Interior-Exterior Self-Leveling Laser Cross Level

Technical Specifications

Ideal Jobs: Interior and Outdoor Jobsite

Laser Diode: Dual 635nm "high powered" diode

Accuracy: $\pm 3/32$ -in @ 30-ft (± 2.5 mm @ 9m)

Range: Up to 100-ft (30m) dependent on illumination of area

Detector Range: Over 100-ft (30m+)

Fan Angle: 130°

Features:

- "Manual Mode Feature" allows tilting for extreme angles
- Out-of-Level Sensor

Line Length: 100-ft @ 30-ft (30m @ 9m)

Leveling Range: $\pm 5^\circ$

Leveling Speed: 3 seconds

Compensator: Gimbal (Ball bearing hung, magnetically dampened)

Power: Three AA batteries 1.5V

Warranty: 1 Year

Model ILMXT Packages

58-ILMXT ILMXT Package. Includes: Laser Level, Magnetic Laser Tripod, and Hard Carrying Case

58-ILMXTE ILMXT Interior-Exterior Package. Includes: Laser Level, Magnetic Laser Tripod, LLD-2 Laser Detector, and Hard Carrying Case



Available at your local CST/berger dealer.

CST/berger

255 W. Fleming Street • P.O. Box 359
Watseka, IL 60970 USA

Phone: 815.432.5237 • Toll Free: 800.435.1859 • Fax: 800.913.0049

www.csts survey.com • sales@csts survey.com

Chicago Steel Tape

Berger Instruments

Magna-Trak®

LaserMark®

Tru-Lock™